

## MAXAttach™

### Expandable Tabletop Conference Phones

The industry's first fully expandable tabletop conference phones. MAXAttach comes with two complete phone units and provides premium, full-duplex audio in medium sized rooms. It also features the ability to link up to two additional phone units for unrivaled microphone and loudspeaker coverage in larger rooms.

**ClearOne®**



UNRIVALED AUDIO  
QUALITY, FLEXIBILITY  
AND AFFORDABILITY

#### MAXATTACH APPLICATIONS

Executive Office  
Medium Conference Room  
Large Conference Room  
Training Room  
Separate Rooms

#### MAXATTACH ADVANTAGES

##### Superior Audio Performance

- + Distributed Echo Cancellation® effectively eliminates echo
- + Noise cancellation removes background noises from fans or HVAC systems
- + Full-duplex sound enables participants to speak and listen at the same time without cutting in and out
- + Automatic level controls keep participants' audio balanced and consistent
- + First-mic priority eliminates hollow "tunnel" sound by activating only the microphone closest to the person speaking
- + Three microphones in each phone unit provide 360° audio pickup

##### Expandability

###### MAXAttach

- + Comes with two phone units and a single base unit for medium conference rooms; also available in 3-phone and 4-phone kits
- + Link up to four complete phones, not just microphones, for expanded coverage with MAX EX Expansion Kits
- + Divide MAXAttach into multiple phone systems for use in separate rooms with MAX EX Expansion Base

###### MAX EX Expansion Kit

- + Includes phone and connecting cable to expand MAXAttach room coverage (base not included)

###### MAX EX Expansion Base

- + Used to divide MAXAttach into multiple phone systems for use in separate rooms to provide unrivaled flexibility and affordability

##### Ease of Use & Control


- + Simply plug base unit into power and phone line, connect the phones, then dial and talk
- + Features user-friendly telephone style controls
- + Speed dial stores 10 frequently dialed numbers
- + Recording output on base unit connects to a recording device to capture both sides of the conversation
- + Linked MAX phones can be operated using the dial pad of any phone – dialing, mute, volume controls, etc.

## > ROOM APPLICATIONS

### MAX EX



### MAXAttach™ (MAX EX + MAX Exp. Kit)




### MAX EX Expansion Kit

Use with any MAX Phone to expand coverage up to 4 total units.


### MAXAttach + 1 Exp. Kit



### MAXAttach + 2 Exp. Kits



### MAX EX Expansion Base



Enables MAXAttach and MAX EX Expansion Kits to be used in separate rooms. Includes power supply and 25' cable.

## > SPECIFICATIONS

### Echo Cancellation

Tail time: 60 ms x 3

### Noise Cancellation

Dynamic noise cancellation

### Telephone Connection

Analog PBX or PSTN line  
RJ-11C, -12 dBm nominal

### Keypad

Alphanumeric standard keypad

### Loudspeaker

Volume: 90dBspl A weighted @ 1 ft  
Bandwidth: 200 Hz–3.3 kHz

### Record Output

Connector: 2.5 mm mono audio jack  
Impedance: <1000 ohms  
Bandwidth: 200 Hz–3.3 kHz  
Dynamic range: 60 dB  
THD <.01%

### Certifications

FCC part 15 Class A  
FCC part 68  
UL Certified

### Power

Base unit:  
Auto-adjusting power module;  
100-240 VAC; 50/60 Hz

### Environmental

Operating temperature: 32–118° F  
(0–48° C)  
Storage temperature: 41–158° F  
(5–70° C)  
Operating humidity: 15 to 80%  
Storage humidity: 10 to 90%

### Dimensions (W x D x H)

Phone unit: 10.5" x 10.5" x 3"  
(26.7 cm x 26.7 cm x 7.6 cm)  
Base unit: 4.25" x 5.5" x 2.5"  
(10.8 cm x 14 cm x 6.4 cm)

### Weight

Phone unit: 2.7 lb (1.2 kg)  
Base unit: .6 lb (0.27 kg)  
Shipping: 10 lb (4.5 kg)

### PART NUMBERS

#### MAXAttach\*

910-158-500-00 (North America)  
910-158-501-00 (Europe/UK - ROHS)  
\* For MAXAttach plus 1, change -00 to -01 in part number; for MAXAttach plus 2, change -00 to -02 in part number.  
910-158-058 (Hong Kong/Singapore)  
910-158-056 (Japan)  
910-158-059 (Australia/New Zealand)  
910-158-060 (South Africa)  
910-158-061 (South Korea)  
910-158-062 (China)

\* For MAXAttach plus 1, add -01 to part number; for MAXAttach plus 2, add -02 to part number.

Includes:  
MAX phone units (2)  
MAX base unit (1)  
12' Cat. 5 cable (1)  
25' Cat. 5 cable (1)  
Telephone cable  
Documentation CD  
Quick start guide

#### MAX EX Expansion Kit

910-158-555 (All countries)

Includes:  
MAX phone unit (1)  
12' Cat. 5 cable (1)  
Documentation CD  
Quick start guide

#### MAX EX Expansion Base

910-158-551 (Europe/UK - ROHS)  
910-158-550 (All other countries)

Includes:  
MAX base unit (1)  
25' Cat. 5 cable (1)  
Telephone cable  
Documentation CD  
Quick start guide



## VODANET

Bestekar Sadettin Kaynak Sok. No:18 Altunizade - ISTANBUL

0216 340 76 40

[www.vodanet.com.tr](http://www.vodanet.com.tr)